


A+++

App
Wi-Fi

Modbus
ready

Gas
refrigerante

Full
inverter

Telecomando
incluso

Wi-Fi
incluso

NERO			EVR9CN	EVR12CN	EVR18CN	EVR24CN
BIANCO			EVR9CB	EVR12CB	EVR18CB	EVR24CB
RAFFREDDAMENTO	Capacità (min-max)	Btu/h	3207 - 12999	3412 - 13648	4265 - 20472	6243 - 25317
	Capacità (min-max)	kW	0,94 - 3,81	1,00 - 4,00	1,25 - 6,00	1,83 - 7,42
	Potenza elettrica assorbita (min-max)	kW	0,24 - 1,36	0,29 - 1,50	0,33 - 2,36	0,41 - 2,80
	EER		3,94	3,36	3,70	3,70
	Pdesignc	kW	2,60	3,50	5,20	7,00
	SEER	W/W	8,50	8,50	8,50	8,50
	Classe Efficienza Energetica		A+++	A+++	A+++	A+++
RISCALDAMENTO	Capacità (min-max)	Btu/h	3207 - 14433	3412 - 15354	4265 - 23202	6312 - 27159
	Capacità (min-max)	kW	0,94 - 4,23	1,00 - 4,50	1,25 - 6,80	1,85 - 7,96
	Potenza elettrica assorbita (min-max)	kW	0,24 - 1,65	0,29 - 1,83	0,34 - 2,75	0,42 - 3,00
	COP		3,90	4,00	3,98	3,96
	Pdesignh (Average)	kW	2,40	2,50	4,20	5,30
	SCOP (Average)	W/W	4,60	4,70	4,60	4,70
	Classe Efficienza Energetica (Average)		A++	A++	A++	A++
	Pdesignh (Warmer)	kW	2,60	3,50	5,00	6,40
	SCOP (Warmer)	W/W	5,3	5,9	5,6	5,6
	Classe Efficienza Energetica (Warmer)		A+++	A+++	A+++	A+++
UNITÀ INTERNA / NERO			EVR9UIN	EVR12UIN	EVR18UIN	EVR24UIN
UNITÀ INTERNA / BIANCO			EVR9UIB	EVR12UIB	EVR18UIB	EVR24UIB
Alimentazione		V-Ph-Hz	220-240, 1 , 50	220-240, 1 , 50	220-240, 1 , 50	220-240, 1 , 50
Portata d'aria (Hi/Mi/Lo)		m3/h	700/570/460	700/570/460	900/700/530	1150/940/750
Livello pressione sonora (Hi/Mi/Lo)		dB(A)	44/34/19	44/34/19	47/33/23	50/37/26
Livello potenza sonora (Hi/Mi/Lo)		dB(A)	54/44/29	54/44/29	57/43/33	60/47/36
Dimensioni nette (LxPxH)		mm	808x209x305	808x209x305	808x209x305	1096x222x333
Dimensioni con imballo (LxPxH)		mm	880x275x375	880x275x375	981x275x375	1165x295x405
Peso Netto/Lordo		kg	9,7/12,2	9,7/12,2	10/13	14,2/ 17,2
UNITÀ ESTERNA / NERO			EVR9UEN	EVR12UEN	EVR18UEN	EVR24UEN
UNITÀ ESTERNA / BIANCO			EVR9UEB	EVR12UEB	EVR18UEB	EVR24UEB
Alimentazione		V-Ph-Hz	220-240, 1 , 50	220-240, 1 , 50	220-240, 1 , 50	220-240, 1 , 50
Livello pressione sonora		dB(A)	52	53	55	58
Livello potenza sonora		dB(A)	62	63	65	68
Dimensioni nette (LxPxH)		mm	787x290x498	810x305x549	927x380x699	978x421x803
Dimensioni con imballo (LxPxH)		mm	818x325x520	835x328x575	949x392x732	1022x480x835
Peso Netto/Lordo		kg	22/24	24/26	38/41	45/48
DATI REFRIGERANTE						
Refrigerante	Tipo		R32	R32	R32	R32
	GWP		675	675	675	675
	Carica di refrigerante	kg	0,57	0,60	0,87	1,27
Tubo refrigerante	Liquido	mm	Ø 6,35 (1/4")	Ø 6,35 (1/4")	Ø 6,35 (1/4")	Ø 6,35 (1/4")
	Gas	(inch)	Ø 9,52 (3/8")	Ø 9,52 (3/8")	Ø 12,7 (1/2")	Ø 12,7 (1/2")
	Lunghezza max linea frigorifera	m	25,0	25,0	25,0	25,0
	Max dislivello	m	10,0	10,0	10,0	10,0
	Precarica refrigerante	m	5,0	5,0	5,0	5,0
Temperatura d'esercizio	FGAS addizionale	g/m	15,0	15,0	15,0	15,0
	Interna (raffred. / riscald.)	°C	17~32/0~30	17~32/0~30	17~32/0~30	17~32/0~30
	Esterna (raffred. / riscald.)	°C	-15~53/-25~30	-15~53/-25~30	-15~53/-25~30	-15~53/-25~30