

9000 / 12000 / 18000 / 24000 BTU/h
A++

 App
Wi-Fi

 Gas
refrigerante


Inverter


 Telecomando
incluso

 Wi-Fi
incluso

MODELLO			EVT9CB	EVT12CB	EVT18CB	EVT24CB
RAFFREDDAMENTO	Capacità (min-max)	Btu/h	3100 - 11600	3800 - 13400	6200 - 19900	7100 - 27000
	Capacità (min-max)	kW	0,90 - 3,40	1,11 - 4,16	1,81 - 6,12	2,08 - 7,95
	Potenza elettrica assorbita (min-max)	kW	0,10 - 1,24	0,13 - 1,58	0,56 - 2,05	0,42 - 3,15
	Pdesignnc	kW	2,60	3,50	5,30	7,00
	SEER	W/W	7,00	6,50	7,40	6,10
	Classe Efficienza Energetica		A++	A++	A++	A++
RISCALDAMENTO	Capacità (min-max)	Btu/h	2800 - 11500	3700 - 14200	4700 - 19960	5500 - 27000
	Capacità (min-max)	kW	0,82 - 3,37	1,08 - 4,22	1,37 - 5,85	1,61 - 7,91
	Potenza elettrica assorbita (min-max)	kW	0,12 - 1,20	0,16 - 1,40	0,78 - 2,00	0,30 - 2,75
	Pdesignh (Average)*	kW	2,30	2,80	4,10	4,80
	SCOP (Average)*	W/W	4,10	4,10	4,00	4,00
	Classe Efficienza Energetica (Average)*		A+	A+	A+	A+
	Pdesignh (Warmer)**	kW	2,30	3,00	4,50	6,10
	SCOP (Warmer)**	W/W	5,10	5,20	5,20	5,00
	Classe Efficienza Energetica (Warmer)**		A+++	A+++	A+++	A++
UNITÀ INTERNA			EVT9UIB	EVT12UIB	EVT18UIB	EVT24UIB
Alimentazione		V-Ph-Hz	220-240, 1, 50	220-240, 1, 50	220-240, 1, 50	220-240, 1, 50
Portata d'aria (Hi/Mi/Lo)		m3/h	435/333/259	530/430/310	840/680/540	980/817/662
Livello pressione sonora (Hi/Mi/Lo/Si)		dB(A)	37/32/25/21,5	39,5/35,5/25/21,5	42,5/36/26/20	45/40,5/36/31
Livello potenza sonora (Hi)		dB(A)	50,0	55,0	56,0	59,0
Dimensioni nette (LxPxH)		mm	715x194x285	805x194x285	957x213x302	1040x220x327
Dimensioni con imballo (LxPxH)		mm	780x270x365	870x270x365	1035x295x380	1120x405x310
Peso Netto/Lordo		kg	6,7/8,8	7,3/9,5	10/13	12,3/15,8
UNITÀ ESTERNA			EVT9UEB	EVT12UEB	EVT18UEB	EVT24UEB
Alimentazione		V-Ph-Hz	220-240, 1, 50	220-240, 1, 50	220-240, 1, 50	220-240, 1, 50
Potenza max assorbita		kW	2,15	2,15	2,50	3,50
Livello pressione sonora		dB(A)	55,0	55,0	56,0	59,0
Livello potenza sonora		dB(A)	59,0	63,0	63,0	67,00
Dimensioni nette (LxPxH)		mm	720x270x495	720x270x495	805x330x554	890x342x673
Dimensioni con imballo (LxPxH)		mm	835x300x540	835x300x540	915x370x615	995x398x740
Peso Netto/Lordo		kg	21/22,8	21/22,8	32,7/35,4	42,9/45,9
DATI REFRIGERANTE						
Refrigerante	Tipo		R32	R32	R32	R32
	GWP		675	675	675	675
	Carica di refrigerante	kg	0,47	0,52	1,08	1,42
Tubo refrigerante	Liquido	mm	Φ6,35(1/4")	Φ6,35(1/4")	Φ6,35(1/4")	Φ9,52(3/8")
	Gas	(inch)	Φ9,52(3/8")	Φ9,52(3/8")	Φ12,7(1/2")	Φ15,9(5/8")
	Lunghezza max linea frigorifera	m	25,0	25,0	30,0	50,0
	Max dislivello	m	10,0	10,0	20,0	25,0
	Precarica refrigerante	m	5,0	5,0	5,0	5,0
Temperatura d'esercizio	FGAS addizionale	g/m	12,0	12,0	12,0	24,0
	Interna (raffred. / riscald.)	°C	17~32/0~30	17~32/0~30	17~32/0~30	17~32/0~30
	Esterna (raffred. / riscald.)	°C	-15~50/-20~30	-15~50/-20~30	-15~50/-15~30	-15~50/-15~30

*Tbiv = -7°C

**Tbiv = +2°C